



## McKenzie-Martin Ltd

### Ventilators - Louvres - Rooflights

Eton Hill Works, Eton Hill Road, Radcliffe, Manchester M26 2US  
Tel: 0161 723 2234 Email: [sales@mckenziemartin.co.uk](mailto:sales@mckenziemartin.co.uk)  
Fax: 0161 725 9531 Website: [www.mckenziemartin.co.uk](http://www.mckenziemartin.co.uk)

### Kenstack Roof Ventilator – L10 NBS Spec

- **Manufacturer:** McKenzie Martin Ltd, Eton Hill Works, Eton Hill Road, Radcliffe, Manchester M26 2US; Tel: 0161 723 2234 Email: [Sales@mckenziemartin.co.uk](mailto:Sales@mckenziemartin.co.uk)  
Web: [www.Mckenziemartin.co.uk](http://www.Mckenziemartin.co.uk)
- **Product Reference:** Kenstack Roof Mounted Vent
- **Description:** Roof mounted natural exhaust ventilator. Comprising of external body containing top canopy, drainage outlets, throat and base skirt assembly.
- **Throat Width:** 152mm / 203mm / 254mm / 305mm / 381mm / 457mm / 508mm / 610mm / 762mm / 914mm
- **Overall Length:** Individual units from 1220mm to 2948mm. Units can be joined together to form continuous runs
- **Measured Free Area:** 48% to 69% (dependent upon throat width)
- **Coefficient of Discharge:** 0.24
- **Material:** 1.2mm Aluminium 1050A H14 / 0.7mm hot dip galv, plastic coated one side (Except 914mm models) / 0.7mm hot dip galv, plastic coated both sides (Except 914mm models) / 0.9mm galvanised mild steel
- **Finish:** Mill Finish Aluminium / Polyester Powder Coated / Marine Grade Polyester Powder Coated / Leathergrain, Standard stock colour / Galvanised
- **Mesh:** Aluminium bird diamond mesh 35 x 12 / Aluminium fly diamond mesh 3.5 x 2
- **Damper:** Permanently Venting / Integral Damper (Only available on units from 254mm to 914mm)
- **Method Of Operation:** Permanently ventilating / Cable operation to Clam Cleat / Cable operation to Winch / Pneumatic Actuation / 230v Actuator / 24v Actuator
- **Fixing:** Units to be installed in line with manufacturer's instructions by a competent installer