

## McKenzie-Martin Ltd

## Ventilators - Louvres - Rooflights

Eton Hill Works, Eton Hill Road, Radcliffe, Manchester M26 2US Tel: 0161 723 2234 Email: sales@mckenziemartin.co.uk Fax: 0161 725 9531 Website: www.mckenziemartin.co.uk

## Mackridge Roof Ventilator - L10 NBS Spec

- Manufacturer: McKenzie Martin Ltd, Eton Hill Works, Eton Hill Road, Radcliffe, Manchester M26 2US; Tel: 0161 723 2234 Email: <a href="mailto:Sales@mckenziemartin.co.uk">Sales@mckenziemartin.co.uk</a>
  Web: <a href="mailto:www.Mckenziemartin.co.uk">www.Mckenziemartin.co.uk</a>
- Product Reference: Mackridge Ridge Mounted Vent
- **Description:** Ridge mounted natural exhaust ventilator. Comprising of external body containing top canopy, drainage outlets, throat and base skirt assembly.
- Throat Width: 152mm / 203mm / 254mm / 305mm / 381mm / 457mm / 508mm / 610mm / 762mm / 914mm
- Overall Length: Individual units from 1220mm to 2948mm. Units can be joined together to form continuous runs
- Measured Free Area: 48% to 69% (dependent upon throat width)
- Coefficient of Discharge: 0.24
- Material: 1.2mm Aluminium 1050A H14 / 0.7mm hot dip galv, plastic coated one side (Except 914mm models) / 0.7mm hot dip galv, plastic coated both sides (Except 914mm models) / 0.9mm galvanised mild steel
- Finish: Mill Finish Aluminium / Polyester Powder Coated / Marine Grade Polyester Powder Coated / Leathergrain, Standard stock colour / Galvanised
- Mesh: Aluminium bird diamond mesh 35 x 12 / Aluminium fly diamond mesh 3.5 x 2
- **Damper:** Permanently Venting / Integral Damper (Only available on units from 254mm to 914mm)
- Method Of Operation: Permanently ventilating / Cable operation to Clam Cleat / Cable operation to Winch / Pneumatic Actuation / 230v Actuator / 24v Actuator
- Fixing: Units to be installed in line with manufacturer's instructions by a competent installer