



McKenzie-Martin Ltd

Ventilators - Louvres - Rooflights

Eton Hill Works, Eton Hill Road, Radcliffe, Manchester M26 2US

Tel: 0161 723 2234

Email: sales@mckenziemartin.co.uk

Fax: 0161 725 9531

Website: www.mckenziemartin.co.uk

Operating Box Louvre 130 – L10 NBS Spec

- **Manufacturer:** McKenzie Martin Ltd, Eton Hill Works, Eton Hill Road, Radcliffe, Manchester M26 2US; Tel: 0161 723 2234 Email: Sales@mckenziemartin.co.uk
Web: www.Mckenziemartin.co.uk
- **Product Reference:** Operating Box Louvre (OBL) 130
- **Description:** Operating louvre with adjustable pivoting louvre blades
- **Louvre Blade Pitch:** 130mm
- **Overall Depth:** 203mm
- **Measured Free Area:** 80% (Fully opened)
- **Coefficient of Discharge:** 0.45
- **Material:** 1.2mm Aluminium 1050A H14 / 0.7mm hot dip galv, plastic coated one side (Plastisol) / 0.7mm hot dip galv, plastic coated both sides (Plastisol) / 0.9mm galvanised mild steel
- **Finish:** Mill Finish Aluminium / Polyester Powder Coated / Marine Grade Polyester Powder Coated / Leathergrain, Standard stock colour (Plastisol) / Galvanised
- **Mesh:** Aluminium bird diamond mesh 35 x 12 / Aluminium fly diamond mesh 3.5 x 2
- **Method Of Operation:** Manual Friction Loaded, Hand Operation / Manual Friction Loaded, Pole Operation / Cable operation to Clam Cleat / Cable operation to Winch / Pneumatic Actuation / 230v Actuator / 24v Actuator
- **Blanking Plates:** None / Single skin 1.5mm aluminium / Double skin insulated or acoustic 1.5mm aluminium
- **Fixing:** Louvres to be installed in line with manufacturer's instructions by a competent installer